

## Brickwork Specifications

Model: Quadra-Fire Voyageur Grand Insert  
Vent: Vertical Termination  
Capacity: Heats up to 260m<sup>2</sup> (Average)  
Fuel: Wood

### Finished Brickwork Opening Requirements:

Height: 630mm minimum to 760mm maximum  
Note: Base to be solid and level, add height of hearth if applicable. The opening lintel can only be one brick in width.  
Width: 880mm minimum to 1040mm maximum  
Depth: 490mm minimum

### Other Requirements:

Flue: Brick Working Chimney – Combination of 150mm diameter stainless steel rigid and flexible flue with cowl and standard size chimney plate. Overall height is determined by how high and far away the highest point of the roof is.

Brick Void Chimney – 150mm diameter stainless steel rigid flue, cowl and standard size chimney plate. Overall height is determined by how high and far away the highest point of the roof is.

Brick void to ceiling – 150mm diameter stainless steel rigid flue used within brickwork, adapted to 250mm overall diameter aircooled flue through the ceiling and roof space. Overall height is determined by how high and far away the highest point of the roof is.

Power: Provide a single non switch GPO/413 Socket and locate close to the bottom right side within the opening and power isolation switch to the face of the room wall.

Access: Scaffolding must be provided if no safe access to roof (every multi storey building and roof over 6m high)

\*Please read the installation in full to ensure all requirements are met.