

Brickwork, Gas & Power Specifications

Model: i30 Series
Vent: Vertical or Horizontal Termination
Capacity: i30 Series heats up to 80m² on high (on average with standard height ceilings)

Finished Brickwork Opening Requirements (Exact):

Height: 550mm Note: Base to be solid and level, add height of hearth if applicable. The opening lintel can only be one brick in width.
Width: 800mm
Depth: 400mm

Other Requirements

Cavity: No combustibles to be within same cavity – This model does not come with Zero Clearance.

Gas: Provide a crimped/capped off copper gas line to suit 60mj and locate close to the bottom left hand side within the opening. Note: No composite pipe to be within same cavity.

Power: Provide a single non switch GPO/413 socket and locate close to the bottom right hand side within the opening and a power isolation switch to the face of the room wall.

Flue: Full Brick Chimney (No combustibles) – Non-insulated 75mm dual flexible flue used. Ensure that termination clearances are met. This is a gas regulation and cannot be overlooked.

Non Brick Chimney (ie: With roof space) – Non-insulated 75mm dual flexible flue used to top of brickwork cavity and is then adapted to insulated flue. Ensure a clear path is made available through to the roof space and that termination clearances are met. This is a gas regulation and cannot be overlooked.

Access: Scaffolding is required for all multi storey installations.

Room Vents: Not required for Balanced Flue fireplaces.