

QUADRA-FIRE®

NOTHING BURNS LIKE A QUAD

How to use a Quadra Fire Slow combustion with ACC

1. Place fire lighters and/or newspaper crunched into small balls into the middle of the firebox with small kindling over the top of this.
2. Set larger pieces of wood on top of the kindling/paper loading the timber in a North / South configuration (This is different from Australian slow combustions which load east / west) You should load smaller pieces onto first and then larger pieces last
3. Fill the firebox to 2/3 full
4. Open the primary air shutter and set to full open
5. Open the secondary air shutter to full by pushing the ACC lever fully back. You will feel resistance as the timer is activated. Once pushed back, pull the ACC lever forward to the desired level (For a cold start, this should be full open)
6. Light the fire and shut the door and let the ACC take care of the air control
7. After a good level of hot coals has built up in the firebox, you can start to shut down the secondary air. After this is done you can control the speed of the fire by the primary air control.
8. Always make sure there is flame inside the firebox, if you lose flame open the primary air more. Failure to have flame will result in a smouldering and dirty fire which will not “quad burn”. This also will affect the air wash on the glass and will result in dirty glass.
9. When re loading with more wood, ensure you activate the ACC by pushing the secondary lever back, if the fire is hot, pull the lever all the way forward so the ACC will shut down the secondary air after 20 minutes. By activating the ACC on re load, you are increasing the efficiency of the fire and ensuring a true Quad Burn.
10. Always leave a layer of ash or coals to burn on when cleaning the firebox. This will make the fire easy to start and help with the longevity of the fire bricks.

Load, light, live!

